



## Features

- High resolution LCD monitor
- Expandable 3 channel camera input
- Heavy duty U shape mounting bracket
- Sony CCD image sensor
- IR night vision capability
- Remote control included
- Mirror and normal image switch function
- Programmable parking guidelines
- Built-in microphone and sound capability
- Wide voltage input: DC 10V – 32V
- Waterproof camera: IP69K
- Complete plug and play solution
- Two year warranty

## Specifications for LCD703

|                         |                             |
|-------------------------|-----------------------------|
| Housing Colour          | Black                       |
| Display Size            | 7 inch                      |
| Type of Display         | TFT                         |
| Camera Inputs           | 3 AV input                  |
| Standard (PAL/NTSC)     | Yes                         |
| Auto Detect             | Yes                         |
| Video Output            | CVBS signal                 |
| Standard (PAL/NTSC)     | Yes                         |
| Resolution              | 800*RGB*480                 |
| Brightness              | 500cd/m2                    |
| Guidelines              | Yes                         |
| Mirror Function (V/H)   | Yes                         |
| Picture Adjustable      | Yes                         |
| Loudspeaker             | Yes                         |
| Menu Languages          | English, Simplified Chinese |
| Remote Control          | Yes                         |
| Operating Voltage       | DC10-32V                    |
| Current Consumption     | 5W                          |
| Cable Length at Monitor | 30cm                        |
| Operating Temperature   | -20°C ~ +70°C               |
| Storage Temperature     | -30°C ~ +80°C               |
| Housing Material        | ABS                         |
| Trigger                 | 3                           |
| Bracket                 | U bracket                   |
| Sunshade                | Removable                   |

## Specifications for CAM155

|                        |                 |
|------------------------|-----------------|
| Housing Colour         | Black           |
| Image Sensor           | SONY            |
| Type (CMOS/CCD)        | CCD             |
| Resolution             | 700TVL          |
| Viewing Angle (V/H/D)  | D/150°          |
| Standard (PAL/NTSC)    | NTSC            |
| IR Illumination        | Yes             |
| Light Sensitivity      | AUTO            |
| Backlight Compensation | AUTO            |
| White Balance          | AUTO            |
| Mirror Function        | Mirror          |
| Operating Voltage      | 12V             |
| Cable Length at Camera | 30cm            |
| Operating Temperature  | -20°C ~ +70°C   |
| Storage Temperature    | -30°C ~ +80°C   |
| Protection Class       | IP69K           |
| Audio                  | YES             |
| Mechanical Vibration   | 4G              |
| Housing Material       | Aluminium alloy |

### Main Component Parts List:

- 1 - Monitor x 1pc
- 2 - Monitor sunshade cover x 1pc
- 3 - Camera x 1pc
- 4 - Power cable x 1pc
- 5 - Adaptor cable x 1pc
- 6 - Extension cable x 1pc
- 7 - Remote control x 1pc
- 8 - Installation Kits x 1bag
- 9 - Manual x 1pc