



Features of LCD714WHD

7" LCD colour monitor with HD 1024 x 600P high resolution display
 Expandable 4/2/1 channel camera input
 Wireless range of up to 200m transmission distance (line of sight)
 Automatic pairing function of monitor & camera(s)
 Night-vision function (IR) 7" monitor with inbuilt DVR
 SD card data storage
 Quad, split or single screen display
 Mirror and normal image switch available
 Programmable parking guidelines
 Built-in microphone and sound capability
 Wide voltage input: DC 9V – 36V
 Waterproof: IP68
 Vibration: 10G
 Loudspeaker
 Two year warranty

Specifications for LCD714WHD

Image (Main Chip)	7.0" LCD monitor
Transmission Frequency	2.4G (digital)
Transmission Resolution	High definition
Transmission Delay (Ave)	120mS
RF Pairing	Auto
Changeable Channel	125 CH (overlapping hopping channel)
Voltage	DC9 ~ 36V
Consumption	< 3W
Brightness	500cdm
Mirror Image	Yes (via menu select)
Speaker	Yes
Contrast / Brightness	Yes
Camera Selection	1-4 (auto or manual)
Dimensions	187W x 121H x 24D mm
Weight	400g
Temperature	-20°C to +70°C



Features of CAM155WHD

HD1080P high resolution, super wide angle lens
 Wireless range of up to 200m transmission distance (line of sight)
 Automatic pairing function of monitor & camera(s)
 Night-vision function (IR)
 Mirror and normal image switchable
 Built-in microphone
 Wide voltage input: 9V ~ 36V system
 Waterproof: IP69K
 Vibration: 10G
 Firm structure: aluminum-alloy housing, anti-UV surface painting
 Angle adjustable
 Two year warranty

Specifications for CAM155WHD

Image (Main Chip)	1/2.7" CMOS BSI color 1920H x 1080V pixels
Voltage	DC9 ~ 36V
Consumption	< 1W
Lens Angle	120° diagonal
Microphone	Yes
White LED Switch Control	Photo sensor automatic control
Infrared	6 (10m visibility)
Housing	Aluminium alloy
Mechanical Vibration	10G
Mounting	Permanent tilt bracket
Dimensions	87W x 77H x 75D mm
Weight	272g
Temperature	-40°C to +85°C
Ingress Protection	IP69K